

~~SECRET~~ ~~NOFORN~~ ~~INTERNAL USE ONLY~~

6 December 1945


MEMORANDUM FOR: Chief, CSD

Declass Review by NGA.

THROUGH : Chief, Ref/CSD

SUBJECT : Video Tape Collection and Exploitation Programs

On Thursday, 2 December, I spent an hour with [redacted] FBID in his office in the Key Building. [redacted] is an electronics engineer, and I was referred to him when I called [redacted] the chief engineer of FBID, whom I have dealt with before on the [redacted] TV Operation. [redacted] recently accompanied [redacted] Chief, Film Branch, OCR/OR, on a trip to FTD to discuss the [redacted] Program.



The procedure in operations "2" and "3", is to have the proper radio broadcast monitor operate the camera, using his best judgement as to what is important. FBID receives no requirements from OCR/OR, but sends them all photos taken.

[redacted] was either unwilling or unable to go into FBID's future plans for new stations. He indicated that this subject is currently under discussion within FBID. I requested that I be advised if these discussions resulted in a proposal or plan. He agreed.

[redacted] however, did indicate that Bloc TV reception was possible in the following areas:



~~SECRET~~ ~~NOFORN~~ ~~INTERNAL USE ONLY~~

*BEST COPY*

*Available*

*THROUGHOUT  
FOLDER*

6/24/98

~~SECRET~~ ~~NPIC INTERNAL USE ONLY~~

SUBJECT : Video Tape Collection and Exploitation Programs

He also mentioned that FBID was considering portable systems that could be dispatched to one of these areas during a crisis.

[ ] also provided some details about the various world TV systems:

1. US standard = 525 scanlines @ 60 cycles
2. UK standard = 405 scanlines @ 50 cycles
3. Eurovision = 625 scanlines @ 50 cycles
4. France = 819 and 625 scanlines @ 50 cycles
5. German standard = same as Eurovision
6. Intervision = 625 scanlines @ 50 cycles (However, differences in bandwidth and sync pulses)
7. Soviet standard = same as Intervision

[ ] said that FBID's mission as expressed in its charter, overlapped the FTD [ ] program. FBID went along with [ ] as long as it was understood that it was still an FBID mission, and as long as full details on results were provided. These details have apparently not been forthcoming.

The Foreign Services Division (FSD) of FTD is in charge of [ ] [ ] The officer in charge of FSD is [ ] The project engineer is [ ] The program employs a NVH-15 suitcase-sized video tape recorder produced by [ ] [ ] The machine costs about [ ] and employs a 1" tape which is helically scanned. This permits stopping the frame, and the machine at FTD is so modified. In comparison to a 2" system, the 1" system sacrifices about a 25% in definition at both ends of the gray scale, because some of the bandwidth is lost.

FTD has three machines: one at Wright Patterson (modified for stop-frame), one at [ ] and one in [ ] [ ] machines have been modified to meet local conditions. The [ ] machine is operated and maintained by the Air Attache, who has intelligence experience, but of course no electronics competence - this has been one of the problems.

FTD has received authorization to purchase any ex-developed equipment which will convert 1" tape of any scan-line standard to 2" American standard. Neither FBID nor OOR/OR know FTD's dissemination plans when this service becomes available, or when it will be available.

~~SECRET~~ ~~NPIC INTERNAL USE ONLY~~

~~SECRET~~ NPIC INTERNAL USE ONLY

SUBJECT : Video Tape Collection and Exploitation Programs

FBI is quite concerned about television. They have noticed, for instance, that on several occasions recently, important speeches have been broadcast over Moscow local TV only, and not over any other medium that FBI taps.

25X1 [redacted] was also in attendance at a recent KGB TV showing, and commented on it.

[redacted]

25X1

~~SECRET~~ NPIC INTERNAL USE ONLY

**SECRET**

D R A F T  
6 February 1967

MAGNETIC TAPE TO PHOTO REPRODUCER

1. PROBLEM:

To provide the NPIC with a capability it now lacks, i.e., to extract selected high quality still photographs from video tape inputs supplied by the collection community.

2. FACTS BEARING ON THE PROBLEM:

a. Collection programs now being initiated will greatly increase the volume of video tape information available for analysis.

b. Although most video tapes supplied to the collection community can be viewed at some installation, there are no facilities available where tapes can be studied by Center personnel. The Center should have this in-house capability.


c. There are presently no methods of obtaining high quality photo copy or to view selected frames of imagery for study.

d. Except for brightness and contrast controls, there are no electronic methods for enhancement or improving highlight or shadow information.

3. DISCUSSIONS:

a. Current Procedure. Currently when video tapes of intelligence importance are received, analysts are required to travel either to Langley or the Pentagon to view them. Transportation problems for a number of personnel and the need to "study" the taped information (as compared with just "viewing" the taped information) places a burden on both the facility

**SECRET**



**SECRET**

Approved For Release 2005/06/23 : CIA-RDP78B04770A002700040001-9

and personnel. Of the four government agencies which have the facilities for viewing video tape (CIA/Graphic Register, Naval Photographic Center, NSA, and Army Signal Corps) none have the capability of extracting high quality still photographs. It is fully expected that the Center's facilities will be available to the Intelligence Community to fill the specialized needs of the community.

Present photographic hard copy production methods are either (a) Video tape, to 16mm film, to still copy, or (b) uncontrolled direct photography of the video monitor.

The 16mm Kinescope photography obtained from original video tape information is of such poor quality that it is practically useless for detailed analysis. First of all, the technique of Kinescope photography "throws away" information in the conversion from a 30 frame per sec. system to a 24 frame per sec. motion picture display. Secondly, there is considerable loss of information from regeneration in another step from the original and the system is greatly compromised for the purpose of frame comparison study--particularly if there is much motion in the frame. Photographing a video screen produces a very poor copy due to CRT curvature and imperfections. It is also opportunistic and non-selective by its nature. An optimum system would allow the interpreter to select the best frame or best field, (in the event of considerable motion) for evaluation.

b. Origin of Concept. Sparked by the 1 May and 7 November 1965 Moscow parades broadcast on TV and the appearance of other intelligence information on foreign TV programs, CSD requested an investigation, study, and recommendation of TV magnetic tape systems with a quality hard copy capability for the purpose of exploiting this new source of information.

**SECRET**

The requirements as set forth by CSD to achieve NPIC interpretation needs are as follows:

1. Equipment to view and to study video taped information at the Center.

2. Ability to electronically enhance the CRT presentation in order to optimize the pictorial presentation of the particular area of investigation.

3. Ability to extract high quality selected still photographs from the video tape.

c. Proposed Program. The proposed development provides for the design of an electro-optical system for viewing and studying intelligence information in the form of magnetic video tape and for the selection and transfer of this information to a quality photographic record. Incorporated in the system are additional PI aids for image enhancement, black and white stretch, spot wobble, etc.

The proposed program also provides for the operation, maintenance and training services of a field engineer for the period of one year. It is expected that the Center will provide personnel to be trained to take over these duties. If qualified competent Center personnel are not available at the end of this year's time, additional contract personnel can be provided for as long as is necessary.

d. Selection of Contractor. Request for proposals were sent to eleven representative video-electronic firms. Seven "no bids" were received. Proposals were recieved  Evaluation of the proposals was performed by a committee from CSD and cognizant technical personnel from the Technical Development Staff. The results of the evaluation

**SECRET**

Approved For Release 2005/06/23 : CIA-RDP78B04770A002700040001-9

~~is~~ <sup>are</sup> generally as follows:

25X1 1. [ ] Despite the fact that "Horizontal Aperture Equalization" was omitted, the proposal was a very good one and was responsive to the RFP. The price of over half a million dollars is considered prohibitive.

25X1 2. [ ] This proposal is considered non-responsive to the Development Objective. The [ ]  
25X1 [ ] proposes making photo hard copy directly from a narrow band width VOR-250 disc recorder.

25X1 3. [ ] This proposal describes the use of a wide band width recorder not yet in existence. There is a high risk in this approach, which is not necessary. Far better quality can be obtained directly from the video tape.

25X1 4. [ ] This firm proposes the production of hard copy directly from the video tape. The stop motion disc is to be used only for the selection and study of the particular frame or field and for adjustment of the controls. This proposal is considered the best received and is completely responsive to the Development Objective.

f. Alternatives. Without the proposed system for extracting quality photo hard copy from video tapes supplied by the collection community, the only other form of photographic material available is a highly compromised, poor quality 16mm Kine film recording.

**SECRET**

**SECRET**

4. CONCLUSIONS:

25X1 In response to the RFP for a "Magnetic Tape to Photo Reproducer" the [ ] proposal is the best received. It is considered that the proposal will fill the Center's requirements in the present and near future for the production of quality photo hard copy with the highest information content possible from the video tape received from the collection community.

5. RECOMMENDATIONS:

25X1 In keeping with the Center's responsibility to lead the Intelligence Community in the exploitation of intelligence imagery, it is highly recommended that the [ ] proposal for a "Magnetic Tape to Photo Reproducer" for  
25X1 [ ] be accepted.

**SECRET**

D R A F T  
6 February 1967  
TAB B

## TECHNICAL SPECIFICATIONS FOR MAGNETIC TAPE TO PHOTO REPRODUCER

The primary considerations for the operation of the assembled equipment are as follows:

- a. Photographic hard copy quality <sup>*compared to*</sup> stored data quality.

The ultimate R&D objective is to provide a method for producing the highest possible quality photographic hard copy from video tape information provided by the collection community.

- b. Electronic enhancement


Particular emphasis is place upon the ability to examine (slow motion), study (stop motion) and select particular sequence, frames and/or fields\* of video information. It is necessary to use the most advanced electronic techniques to optimize the image or particular parts of the image, i.e. a dark shadow.

In addition to brightness and contrast controls the equipment will have:

1. "Spot Wobble" - Control for reducing or eliminating the appearance of scan lines.
2. Verticle apertrue Equalizing - verticle scan line enhancement.

\* A single field would be used for optimum image information in the case of excessive motion of the particular subject of interest.

~~SECRET~~



**SECRET**

3. Horizontal aperture Equalizing - horizontal enhancement.
4. Gamma control or "black stretch" - shadow enhancement.
5. Exponential control or white stretch - highlight enhancement.
6. Dropout Compensator - *circuitry for removing white streaks due to imperfections in the video tape.*
- c. Reliability, low maintenance, and ease of operation.

The basic components shall be of the highest commercial quality. Where possible, solid state components will be used. Particular efforts will be made to minimize RFI. Circuitry and shielding shall be designed and fabricated to keep the RFI of interface components at least equal to or less than the basic commercial components of the assembly.

The man-machine interface shall be designed for ease of operation without over simplification to the point of sacrificing machine performance or special functions. Equipment should be designed to facilitate testing and maintenance of the components.

- d. Ability to handle various standards.

The assembled equipment will be able to handle the following standards both high and low land.

1. 525/60
2. 525/50
3. 405/50

The equipment will be amendable to modification without extensive changes, to color TV when the source becomes readily available.

**SECRET**

SENDER WILL CHECK CLASSIFICATION TOP AND BOTTOM					
UNCLASSIFIED		CONFIDENTIAL		SECRET	
CENTRAL INTELLIGENCE AGENCY OFFICIAL ROUTING SLIP					
TO: NAME AND ADDRESS		DATE		INITIALS	
[Redacted]		3 JAN 1961		[Signature]	
5					
6					
ACTION		DIRECT REPLY		PREPARE REPLY	
APPROVAL		DISPATCH		RECOMMENDATION	
COMMENT		FILE		RETURN	
CONCURRENCE		INFORMATION		SIGNATURE	
Remarks:					
<p><i>Thank - for your letter - of - action letter</i></p> <p>[Redacted]</p> <p>[Redacted]</p>					
FOLD HERE TO RETURN TO SENDER					
FROM: NAME, ADDRESS AND PHONE NO.				DATE	
[Redacted]				3 JAN 1961	
UNCLASSIFIED		CONFIDENTIAL		SECRET	

FORM NO. 2-61 237 Use previous editions

(40)  
U.S. GOVERNMENT PRINTING OFFICE : 1961 O-587282

FROM:

*Chief CSD*

DATE:

*20 DEC*

	TO	INITIALS	DATE	REMARKS
DIR				
DEP/DIR				
EXEC/DIR				
TECH ADV	✓	<i>JWC</i>		
ASST FOR ADMIN				
CH/SS				
CH/MSS				
ASST FOR OPS				
ASST FOR PA				
ASST FOR P&D	✓			
CH/CSD				
CH/IPD				
CH/PD				
CH/PSD				
CH/TID				
CH/CIA/PID				
CH/DIA/XX-4				
CH/DIA/AP-IP				
CH/SPAD				
LO/CGS/CIA				
LO/NSA				

*FOR YOUR INFORMATION -  
ADDITIONAL INFORMATION  
ON THE VIDEO TAPE  
PROBLEM - THIS INFORMATION  
WILL BE DISCUSSED WITH*

*In addition, I left*

*names, numbers, et al  
with [redacted] in  
Follow up request of  
ACL - [redacted]*

25X1

25X1

25X1

25X1

25X1